



WORLDLAWN®

VIPER

- 46", 50" and 60" deck options
- Fabricated steel deck with front reinforcement
- Hydro-Gear EZT transmission on 46" mower
- Hydro-Gear ZT 2800 transmission on 50" and 60" mower
- Discharge, mulch, or collect



EXCEPTIONAL VALUE, WORLD-PROVEN PERFORMANCE



WORLDLAWN®



WORLDLAWN®

VIPER ZERO TURN / SPEC SHEET

VIPER

ENGINE

Manufacturer: 46", 50", 60": Briggs & Stratton
44 V-Twin Vertical
50", 60": Kawasaki FR691V-Twin

HP: 46", 50", 60": 26HP*
50", 60": 23HP*

Displacement: 44 V-Twin Vertical: 656CC
FR691V-Twin: 726CC

Cooling: Air cooled

Air Cleaning: 2 stage foam prefilter

Engine Warranty: 3 years

Per SAE: J1995, J1940*

DRIVE SYSTEM

Type: Hydrostatic transaxle

Transmission: 46": Hydro-Gear EZT
50", 60": Hydro-Gear ZT 2800

Reservoir Capacity: 8 oz

Parking Brakes: Integrated - "auto set"

Speed: 7 mph

DIMENSIONS

MODEL:	WYRZ46S20BS	WYRZ50U26BS	WYRZ50U24KW	WYRZ60U24KW	WYZ6027KWH
Cut Width:	46"	50"	50"	60"	60"
Height:	39.8"	39.8"	39.8"	39.8"	39.8"
Length:	71.7"	72"	72"	72"	72"
Width:	55"	59"	59"	68.5"	68.5"
	47.5" w/deflector up	51" w/deflector up	51" w/deflector up	61" w/deflector up	61" w/deflector up
Wheel Base:	44"	46.3"	46.3"	46"	46.3"
Wheel Track:	30" front 33.8" rear	30" front 33.8" rear	30" front 33.8" rear	30" front 33.8" rear	30" front 33.8" rear
Weight:	544 lbs	590.84 lbs	590 lbs	637 lbs	637 lbs

GENERAL

Seat: High-back, foam-padded
internal spring suspension

Fuel Capacity: 3 gallons

Cup Holder: Yes

Front Tire: 11 x 4 - 5 smooth

Drive Tire: 18 x 9.50 - 8 turf

PTO: Warner Electric clutch

DECKS

Cutting Width: 46", 50", 60" Spindles: 3

Cutting Heights: 1.5"-4.5" Deck Belts: 1

Deck Lift: Hand lever Construction: 11 ga. steel w/
front reinforcing bar

Blades: 3 Spindle Mounts: 4 bolt

Blade Length: 16"

EXCEPTIONAL VALUE, WORLD-PROVEN PERFORMANCE



WORLDLAWN®